

# **VIOX SERIES**

SINGLE PHASE HYBRID INVERTER

Low Voltage IP65 Inverters: Performance and Durability Redefined



## **VIOX SERIES**

# **Features**



Max. Efficiency 97.2%



Dual MPPT



BMS Compatible



IP65 Ingress Protection



Dual Output



Internal SDP



Support Generator Connection



Six Time of Use Setting



Support Multiple Parallel



Built In Zero Export



Built in Wi-fi Dongle



Touch Screen Display



5 Years Unlimited Parts Replacement 2 Years Free Service Warranty

	Viox 6kW	Viox <b>8kW</b>
DC input		
Max. power (kW)	9	12
Start-up voltage (V)	100	
Max. voltage (V)	550	
MPPT voltage range / rated voltage (V)	80-500/360	
PV/(Isc) (A)	24	
Max.input current of each component (A)	16	
No. of MPPT	2	
No.of strings per MPPT tracker	1/1	1/2

#### AC output

Rated output power (kVA/kW)	6/6	8/8
Max output power (kVA)	6.6	8.8
Max. output current (A)	28.7	38.3
Grid voltage/range (Vac)	230/176 ~ 270	
Rated grid frequency (Hz)	50/60	
Power factor	1(0.8leading0.8lagging)	
THDi	< 3%	
AC grid type	L+N+PE	

#### **Battery**

/		
Battery voltage range (V)	40~58	
Max. Charging voltage (V)	58	
Max. Charge/discharge current (A)	120/120	160/160
Communication interface	CAN/485	

#### Emergency power output

6/6	8/8
230	
26	34.8
50/60	
≤ 10	
<2%	
	26 26 50,

### General data

ooriorar data		
Battery charge/discharge efficiency	96%	95.6%
Max. efficiency	97.2%	
Europe efficiency	97%	96.5%
MPPT efficiency	99.9%	
Ingress protection	IP65	
Noise emission (dB)	<35	
Operation temperature (°C)	-25 ~ 60	
Cooling	Natural	
Relative humidity	0 ~95% (Non-condensing)	
Operating altitude (m)	0~2000m (Derating over 2000m)	
Dimensions W*D*H (mm)	455×215×385	486×231×530
Net weight (kg)	20.7	25.8
Isolation transformer		
Standby loss (W)	<15	

#### Display and communication

The Property of the Control of the C	
Display	LCD Color Screen
Communication interface RS485/Wifi/GPRS/CAN/DRM	Yes/Yes/Opt/Yes/Yes



128-C, Garden Block, New Garden Town, Lahore. www.anicsun.com info@anicsun.com +92 3111 777 163











